



220V Charging Interface

特点和性能

- 220V 直接充电;
- 体积小, 机构简单, 易于安装
- 高亮度 LED
- 自主运行时间长

Features and Benefits

- Solar Powered Directly
- Compact. Portable and durable
- High luminance LED
- Running long time after fully charged

应用

- 室内照明
- 走廊庭院照明
- 露营及业务作业
- 灾难救生照明

Application

- Indoor Lighting
- Corridor court Lighting
- Camping and field operation
- Lighting disaster lifesaving

Solar LED Lanterns WT-F003 Specification

Product Code	WT-F003
Number of LED Per Lantern	SMD 32PCS
Ingress Protection	IP20
AC Input	220V 50/60Hz
LED information:	
Lamp Brightness	150lumens for high brightness
Lamp Power	3W
Lifetime of LED	LM-80
Color Temperature	5500-6500K
Battery Information:	
Battery Type	Sealed Maintenance Free (SMF) lead acid battery
Battery Back Up	6V 4.5AH *2
AC Charging Time	12-15Hrs
Working Time	3-4Hrs with high brightness;
Packing Information(Lamp Only):	
Unit Dimension	98*98*200
Inner Packing Size	101*101*207
outer Packing Size	580*355*380
Gross Weight Per Box	6.2Kg

Solar LED Lanterns WT-F002 Specification

Operation Information	1. Please read the instructions and fully charged before Use;
	2. Before plugging in an external battery or power supply, please make sure if the power supply is correct;
	3. During the use process, when the LED lamp brightness get dimmed and batteries become fully discharged state, in order to protect the battery, please stop using and charge it in time at this time. Shouldn't charge after the LED lamp is completely no light, because easily lead to excessive discharge battery failure extremely;
	4. Must use more than 8 hours every three months;
	5. Make the lamp off when not in use
	6. When the temperature is below 0 degrees or above 40 degrees, use and charging efficiency will be reduced;
	7. Do not go near water or rain;
Scrap products	1. In order to reduce pollution of the environment, please do not throw the battery, battery to a designated disposal agency or the designated bins.