

Mode: WT-F012-3Classic



3W Solar Panel



220V Charging Interface

特点和性能

- 可以太阳能供电，也可以市电充电；
- 体积小，机构简单，易于安装
- 高亮度 LED
- 自主运行时间长
- 多档位调节

Features and Benefits

- Solar Powered Directly and AC Charging
- Compact. Portable and durable
- High luminance LED
- Running long time after fully charged
- Multi file adjustment

应用

- 室内照明
- 走廊庭院照明
- 露营及业务作业
- 灾难救生照明

Application

- Indoor Lighting
- Corridor court Lighting
- Camping and field operation
- Lighting disaster lifesaving

Solar LED Lanterns WT-F012-3 Specification

| | |
|--|--|
| Product Code | WT-F012-3 |
| Number of LED Per Lantern | SMD 24PCS |
| Ingress Protection | IP20 |
| AC Input | 220V 50/60Hz |
| Solar Charging Input | DC Jack 9V |
| Indicator | Full Charging Indicator |
| LED information: | |
| Lamp Brightness | 550lumens for high brightness 20 Lumens for high brightness |
| Lamp Power | 12W |
| Lifetime of LED | LM-80 |
| Color Temperature | 5500-6500K |
| Battery Information: | |
| Battery Type | Sealed Maintenance Free (SMF) lead acid battery |
| Battery Back Up | 4V 1.6AH |
| AC Charging Time | 20-24Hrs |
| Solar Charging Time | 20-24Hrs |
| Working Time | 0.5Hrs with high brightness; 20Hrs with low brightness; |
| Packing Information(Lamp Only): | |
| Unit Dimension | 110*115*200 |
| Inner Packing Size | 115*115*208 |
| outer Packing Size | 640*480*228 / 8Pcs |
| Gross Weight Per Box | 11.2Kg |
| Solar Panel | |
| Solar LED Panel Type | 3W 9.0V .0.25A Polycrystalline Solar Panel |
| Solar Panel Dimensions | 235*140*17mm |
| Solar Panel connecting cable length | 2M |
| Solar Panel characteristics | A stand at the back of solar panel to maintain 30 degrees facing to the Sun. |

Solar LED Lanterns WT-F012-3 Specification

| | |
|------------------------------|--|
| Operation Information | 1. Please read the instructions and fully charged before Use; |
| | 2. Before plugging in an external battery or power supply, please make sure if the power supply is correct; |
| | 3. During the use process, when the LED lamp brightness get dimmed and batteries become fully discharged state, in order to protect the battery, please stop using and charge it in time at this time. Shouldn't charge after the LED lamp is completely no light, because easily lead to excessive discharge battery failure extremely; |
| | 4. Must use more than 8 hours every three months; |
| | 5. Make the lamp off when not in use |
| | 6. When the temperature is below 0 degrees or above 40 degrees, use and charging efficiency will be reduced; |
| | 7. Do not go near water or rain; |
| Maintenance | 1. solar panel surface clean |
| | 2. The solar panel surface cannot be scratched and damaged. |
| Scrap products | 1. In order to reduce pollution of the environment, please do not throw the battery, battery to a designated disposal agency or the designated bins. |